

STUMPJUMPER FSR EXPERT CARBON EVO 650b



HYP GRN/BLK

KEY FEATURES

- Hot asymmetrical graphic on the FACT 9m carbon FSR frame with slacker, lower EVO geometry, 150mm of travel, full-cartridge bearing pivots, PF30 BB, and 142mm dropouts makes the meanest trail bike out there
- FOX Float CTD Factory shock with Boost Valve, Kashima coating and AUTOSAG features 3 compression settings: Climb, Trail and Descend with Trail and rebound adjust
- 750mm wide mini-rise alloy handlebars control the new RockShox Pike RC fork providing a great blend of stiffness and weight, with great tuning options, 150mm of travel, and a 15mm thru-axle for precise handling
- Lightweight Roval Traverse 142+ All-Mountain wheelset, with DT Swiss internals and spokes, 15mm thru-axle, and a 142+ rear hub spacing for durable, lightweight, and tubeless-ready performance
- 2Bliss Ready Specialized Butcher and Purgatory Control 2.3" tires for premium control on challenging trail conditions
- SRAM's new X01 11-speed drivetrain featuring a custom S-2200 carbon crankset with PF30 spindle, single chainring setup works with SRAM X01 10-42 cassette for premium shifting and a huge gear range
- All-new, hidden Specialized Command Post IR uses a remote lever to adjust saddle height on-the-fly to maximize climbing and descending performance

SPECS

ALL SPECS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

FRAME	FACT 9m carbon front triangle, EVO geometry, FACT IS construction, M5 alloy rear triangle, tapered headtube, carbon PF30 BB, ISCG '05, internal Command Post IR routing, 142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 150mm travel
REAR SHOCK	Custom FOX Float CTD Factory w/ AUTOSAG and Boost Valve, Kashima coating, Climb, Trail, Descend settings and reb adj., 195x51mm
FORK	RockShox Pike, Solo Air spring, tapered alloy steerer, comp, lockout, and reb adj., 15mm thru-axle, 150mm travel
HEADSET	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
STEM	Specialized XC, 3D forged alloy, 4-bolt, 6-degree rise, 31.8mm clamp
HANDLEBARS	Specialized All-Mountain, low-rise, 7050 alloy, 750mm wide, 8-degree backsweep, 6-degree upsweep, 31.8mm
GRIPS	Specialized Sip Grip, light lock-on, half-waffle, S/M: regular, Others: XL thickness
FRONT BRAKE	Shimano XT M-785, hydraulic disc, S/M: 180mm rotor, Others: 200mm
REAR BRAKE	Shimano XT M-785, hydraulic disc, S/M: 160mm rotor, Others: 180mm
BRAKE LEVERS	Shimano XT M-785, hydraulic disc
REAR DERAILLEUR	SRAM X01 Type 2, 11-speed, mid cage
SHIFT LEVERS	SRAM X01, 11-speed, trigger
CASSETTE	SRAM X01 XG-1195, 11-speed, 10-42
CHAIN	SRAM X1, 11-speed w/ power link
CRANKSET	Custom SRAM S-2200 Carbon, PF30 spindle, S: 170mm, Others: 175mm
CHAINRINGS	32T
BOTTOM BRACKET	SRAM PF30, OS press-in bearings, sealed cartridge
RIMS	Roval Traverse 650b, alloy disc, 28mm wide, 27/32h
FRONT HUB	Roval Traverse SL, 15mm thru-axle end caps, 27h
REAR HUB	Roval Traverse 142+, XX1 driver body, 12mm thru-axle, 32h
SPOKES	DT Swiss Super Comp, 2.0/1.65/1.8 stainless
FRONT TIRE	Specialized Butcher Control, 2Bliss Ready, 650bx2.3", foldable aramid bead, 60TPI
REAR TIRE	Specialized Purgatory Control, 2Bliss Ready, 650bx2.3", foldable aramid bead, 60 TPI
INNER TUBES	Ultralight presta valve
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized Command Post IR, 3-position, internally routed adjustable height w/ air spring, remote operated, single bolt head, 30.9mm, S: 100mm travel, Others: 125mm
SEAT BINDER	Specialized 7050 hard anodized alloy, single bolt, 34.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
93314-3402	EXPERT CARBON EVO 650B HYP GRN/BLK		S
93314-3403			M
93314-3404			L
93314-3405			XL

STUMPJUMPER FSR COMP EVO 650b



MET BLK/HYP GRN/MOTO GRN

KEY FEATURES

- Hot asymmetrical graphic on the M5 manipulated alloy frame with 150mm of rear wheel travel, EVO geometry, tapered headtube, 142mm dropouts, PF30 BB, and sealed cartridge bearing pivots pushes the boundaries of trail riding
- FOX Float CTD Evolution shock with ground-breaking proprietary Specialized AUTOSAG features 3 compression settings: Climb, Trail and Descend, and rebound adjust
- RockShox Revelation RC3 150mm fork has a tapered steerer, 15mm thru-axle, 3-position damper: open, medium, and firm, rebound adjust, and lockout for a lightweight trail bike slider capable of ripping technical descents
- Roval rims mated to Specialized Hi Lo hubs, oversized endcaps, a 142+ rear hub spacing, and 12mm thru-axle increase wheel stiffness for more confident riding
- Custom SRAM S-1250 10-speed All-Mountain double-ring shifts fast while the PF30 spindle makes for an efficient and stiff crankset
- 750mm-wide Specialized All-Mountain low-rise handlebar is built to control rough trail riding
- Shimano Deore disc brakes provide great braking power and modulation while the Specialized Butcher and Purgatory tires keep the traction while rolling fast
- SRAM X9, Type2, 10-speed mid-cage rear derailleur and 11-36 cassette for smooth and reliable shifts
- Specialized Command Post BlackLite uses a remote lever to adjust saddle height on-the-fly to maximize climbing and descending performance

SPECS

ALL SPECS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

FRAME	M5 hydroformed tubing, EVO geometry, tapered headtube, PF30 BB, ISCG '05, Command Post BlackLite routing, 142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 150mm travel
REAR SHOCK	Custom FOX Float CTD Evolution w/ AUTOSAG, Climb, Trail, Descend settings and reb adj., 195x51mm
FORK	Custom RockShox Revelation RC3, 3P damper, tapered alloy steerer, 3-position compression and reb adj., 15mm thru-axle, 150mm travel
HEADSET	1-1/8 and 1-1/2" threadless, Campy style upper with 1-1/2" lower, cartridge bearings
STEM	Specialized XC, 3D forged alloy, 4-bolt, 6-degree rise, 31.8mm clamp
HANDLEBARS	Specialized All-Mountain, low-rise, 7050 alloy, 750mm wide, 8-degree backsweep, 6-degree upsweep, 31.8mm
GRIPS	Specialized Sip Grip, light lock-on, half-waffle, S/M: regular, Others: XL thickness
FRONT BRAKE	Shimano Deore M-615, hydraulic disc, Ice Tech pads, S/M: 180mm rotor, Others: 200mm
REAR BRAKE	Shimano Deore M-615, hydraulic disc, Ice Tech pads, S/M: 160mm rotor, Others: 180mm
BRAKE LEVERS	Shimano Deore M-615, hydraulic disc
FRONT DERAILLEUR	SRAM X7, 10-speed, S3 direct mount for DMD, bottom pull
REAR DERAILLEUR	SRAM X9 Type 2, 10-speed, mid cage
SHIFT LEVERS	SRAM X7, 10-speed, w/ MatchMaker clamp
CASSETTE	SRAM PG-1030, 10-speed, 11-36
CHAIN	PC1051, 10-speed, w/ power link, nickel finish
CRANKSET	Custom SRAM S-1250, 7050 alloy arms, 10-speed AM double, PF30 spindle, S: 170mm, Others: 175mm
CHAINRINGS	36/24, w/ alloy guard
BOTTOM BRACKET	SRAM PF30, OS press-in bearings, sealed cartridge
RIMS	Roval 650b, alloy disc, 24mm wide, 32h
FRONT HUB	Specialized Hi Lo disc, sealed cartridge bearings, 15mm thru-axle, 32h
REAR HUB	Specialized Hi Lo disc, double-sealed cartridge bearings, 12mm thru-axle, 32h
SPOKES	DT Swiss Industry, 2.0/1.65/1.8 stainless
FRONT TIRE	Specialized Butcher Control, 2Bliss Ready, 650bx2.3", foldable aramid bead, 60TPI
REAR TIRE	Specialized Purgatory Control, 2Bliss Ready, 650bx2.3", foldable aramid bead, 60 TPI
INNER TUBES	Ultralight presta valve
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Command Post BlackLite, new "alien head" design, 30.9mm height adjustable single bolt, w/ remote adjust lever. S: 100mm travel, Others: 125mm
SEAT BINDER	Forged alloy, single bolt, 31.8mm

PART NO.	DESCRIPTION	COLOR	SIZE
93315-2502	COMP EVO 650B	MET BLK/HYP GRN/MOTO GRN	S
93315-2503			M
93315-2504			L
93315-2505			XL